

Descriptions

- High current application
- Switching application

Features

- Suitable for AF-Driver stage and low power output stages
- Complementary Pair with BC817F


Ordering Information

Type NO.	Marking	Package Code0
BC807F	LA□	SOT-23F

□ : h_{FE} rank

Outline Dimensions

unit : mm



Absolute maximum ratings

(Ta=25°C)

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	V_{CBO}	-50	V
Collector-Emitter voltage	V_{CEO}	-35	V
Emitter-base voltage	V_{EBO}	-5	V
Collector current	I_C	-800	mA
Collector dissipation	P_C	200	mW
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55~150	°C

Electrical Characteristics

(Ta=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Emitter breakdown voltage	BV_{CEO}	$I_C = -1\text{mA}, I_B = 0$	-35	-	-	V
Base-Emitter turn on voltage	$V_{BE(ON)}$	$V_{CE} = -1\text{V}, I_C = -300\text{mA}$	-	-	-1.2	V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$I_C = -500\text{mA}, I_B = -50\text{mA}$	-	-	-700	mV
Collector cut-off current	I_{CBO}	$V_{CB} = -25\text{V}, I_E = 0$	-	-	-100	nA
DC current gain	h_{FE}^*	$V_{CE} = -1\text{V}, I_C = -100\text{mA}$	100	-	630	-
Transition frequency	f_T	$V_{CB} = -5\text{V}, I_E = 10\text{mA}$ $f = 100\text{MHz}$	-	100	-	MHz
Collector output capacitance	C_{ob}	$V_{CB} = -10\text{V}, I_E = 0, f = 1\text{MHz}$	-	16	-	pF

* : h_{FE} rank / 16(A):100 ~ 250, 25(B):160 ~ 400, 40(C):250 ~ 630

Electrical Characteristic Curves

Fig. 1 P_c - T_a




Fig. 2 I_c - V_{BE}




Fig. 3 I_c - V_{CE}




Fig. 4 h_{FE} - I_c





Fig. 5 $V_{CE(sat)}$ - I_c



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.