

Descriptions

- General small signal application
- Switching application

Features

- Low collector saturation voltage
- Collector output capacitance
- Complementary pair with SBT3904


Ordering Information

Type NO.	Marking	Package Code
SBT3906	2A □ ① ②	SOT-23

① Device Code ② Year & Week Code

Outline Dimensions

unit : mm



PIN Connections

- 1. Base
- 2. Emitter
- 3. Collector

Absolute Maximum Ratings

Ta=25°C

Characteristic	Symbol	Rating	Unit
Collector-base voltage	V_{CBO}	-40	V
Collector-emitter voltage	V_{CEO}	-40	V
Emitter-base voltage	V_{EBO}	-5	V
Collector current	I_C	-200	mA
Collector power dissipation	*P_C	350	mW
Junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-55 ~ 150	°C

* : Package mounted on 99.5% alumina 10×8×0.6mm

Electrical Characteristics

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-base breakdown voltage	BV_{CBO}	$I_C = -10\mu A, I_E = 0$	-40	-	-	V
Collector-emitter breakdown voltage	BV_{CEO}	$I_C = -1mA, I_B = 0$	-40	-	-	V
Emitter-base breakdown voltage	BV_{EBO}	$I_E = -10\mu A, I_C = 0$	-5	-	-	V
Collector cut-off current	I_{CEX}	$V_{CE} = -30V, V_{EB} = -3V$	-	-	-50	nA
DC current gain	h_{FE}	$V_{CE} = -1V, I_C = -10mA$	100	-	300	-
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -50mA, I_B = -5mA$	-	-	-0.4	V
Transition frequency	f_T	$V_{CE} = -20V, I_C = -10mA, f = 100MHz$	-	250	-	MHz
Collector output capacitance	C_{ob}	$V_{CB} = -5V, I_E = 0, f = 1MHz$	-	4.5	-	pF
Delay time	t_d	$V_{CC} = -3V_{dc}, V_{BE(off)} = -0.5V_{dc}, I_C = -10mA_{dc}, I_{B1} = -1mA_{dc}$	-	35	-	ns
Rise time	t_r		-	35	-	ns
Storage time	t_s		-	225	-	ns
Fall Time	t_f	$I_{B1} = I_{B2} = -1mA_{dc}$	-	75	-	ns

Electrical Characteristic Curves

Fig. 1 P_C - T_a




Fig. 2 h_{FE} - I_C





Fig. 3 $V_{CE(sat)}$ - I_C



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.